


GLOBALFLOR SOLID 1.0T HETEROGENEOUS VINYL SHEET



TECHNICAL DATA

Type of floor covering	Heterogeneous Vinyl Sheet (100% virgin material)	
Type of backing	Compact	
Total thickness	EN 428	1.0mm
Wear layer thickness	RN 429	0.1mm
Roll width	EN 426	2m
Roll length	EN 426	20m
Weight	EN 430	1350g/m ²
Surface treatment	PUR	
Plastisizer type	EN 14372	Phthalate-free (DOTP)
Wear resistance	EN 429	T
Fire rating	EN 13501	Bfl-s1
Static electrical propensity	EN 1815	< 2kV
Dimension stability	EN 434	≤ 0.1%
Flexibility	EN 435	Excellent
Color fastness	ISO 105-B02	≥ 6
Stain and chemical resistance	EN 423	Good
Impact sound isolation	ISO 717/2	Approx. 2dB
Formaldehyde emission	EN 14041	E1
PCP	EN 14041	ND
Structure	UV coating, High-density wear layer, Fiberglass layer, 100% Virgin material white Backing layer	
Installation method	Full spread adhesive	
Seaming method	Chemical seam seal with cold welding liquid	
Applications	All interior areas	
Package and loading	25rolls per pallet, 10 pallets per 20ft GP, in total 10000sq.m.. Or 13000sq.m. without pallet	

Please note: Globalflor has a policy of continuous product and product data improvement, it reserves the right to change design and specifications without notice. For the latest Technical Data Sheet, please kindly check www.bomeiflor.com