


GLOBALFLOR ULTRAFLEX

RUBBER-PLASTIC SHEET



TECHNICAL DATA		ULTRAFLEX
Type of floor covering		Compact Rubber-plastic Sheet
Total thickness	EN 428	2.0mm
Roll width	EN 426	2m
Roll length	EN 426	20m
Weight	EN 430	2800g/m ²
Wear resistance	EN 429	T
Classification	EN 649	34/43
Fire rating	EN 13501	Cfl-s1
Smoke density	GB 8624	≤750% min
Electrical resistance	EN 1081	2×10 ¹⁰ ohm
Static electrical propensity	EN 1815	< 2kV
Slip resistance	DIN 51130	R9
Residual indentation	EN 433	≈0.03mm
Dimension stability	EN 434	≤0.06%
Flexibility	EN 435	No crack
Color fastness	ISO 105-B02	≥6
Stain resistance	ASTM F925-13	Great after 60mins Can customize iodine-resistance treatment to make its result to Excellent
Chemical resistance	ASTM F925-13	Excellent after 60mins
Effect of castor chair	EN 425	Excellent
Impact sound isolation	ISO 717/2	Approx. 4dB
TVOC	ISO 16000	< 10μg/m ³
Thermal conductivity	EN 14041	0.072W/m-K
Thermal resistance	EN 14041	0.043W/m-K
Formaldehyde emission	EN 14041	E1
PCP	EN 14041	ND
EU REACH 205 SVHCs test	-	ND
Escherichia Coli ATCC8739	ISO 22196	99.90%
Staphylococcus Aurenus ATCC6539P	ISO 22196	99.90%
Structure	UV coating, 0.75mm Compact rubber-plastic homogeneous polymer layer, 0.5mm Polyester cloth layer and 0.75mm Compact rubber-plastic homogeneous polymer layer	
Installation method	Full spread adhesive	
Seaming method	Seamless seal with double-component adhesive	
Applications	Interior commercial areas with high traffic and light industrial areas	
Package and loading	16rolls per pallet, 10 pallets per 20ft GP, in total 6400sq.m.. Or 8000sq.m. without pallet	

Please note: Globalflor has a policy of continuous product and product data improvement, it reserves the right to change design and specifications without notice. For the latest Technical Data Sheet, please kindly check www.bomeiflor.com